

TECHNICAL DATASHEET

36-831, 36-848 TRANSMISSIONSOLJA ATF-U

PERFORMANCE LEVEL

TRANSMISSIONS

- Ford Mercon V / SP / LV
- Ford M2C-202-B
- Honda Z-1 (Except CVT)
- JWS 3309
- BMW 8072B
- MB 236.6/236.7/236.9/236.10/236.11
- Subaru ATF
- Texaco N402
- VW/Audi G-052-162
- LT 71141
- Chrysler ATF/ATF 3+/ATF 4+
- GM Dexron VI • VW G 052 162
- Toyota T-II/IV/WS • Allison TES-295
- Mitsubishi/Hyundai SP II/III • Nissan Matic D/J
- BMW LA2634
- BMW 7045E
- Man 339 V-1 / V-2 / Z-1 / Z-2
- VW/Audi G-055-025-AZ
- Volvo 1161540/97341
- Voith 55.6335.XX (G607)

PROPERTIES

| | |
|-------------------------------|-------------------|
| Appearance: | Low Viscosity Oil |
| Colour: | Red |
| Density @ 15°C: | 0.854 |
| Kinematic Viscosity @ 40°C: | 40.2 |
| (mm ² /s) @ 100°C: | 7.20 |
| Viscosity Index (VI): | 198 |
| Pour Point (°C): | -52 |
| Flash Point (°C): | 212 |